



Telematic+ Marketing
Transport Technology

Overview YAMS Product Range VR903

VR903MX is the basic unit equipped with standard SUB-D interface connection for engine idling time record. The second interface USB connection is serving the data communication for the Tally Stick TS153 for up/downloads.

VR903RMX has additionally a 12- position dial switch for the user to choose at random various conditions to record important events. Other than that, this unit is the same as VR903MX.

VR903L has an LCD display, three touch buttons with multiple entry below the display. For the user to choose. Other than that, it is identical as VR903MX.

VR903MXG is the same as the basic unit VR903MX but is equipped for GSM (global system for mobile communication)

VR903RMXG is the same as the basic unit VR903RMX but is equipped for GSM (global system for mobile communication)

VR903LG is the same as the basic unit VR903L but is Equipped for GSM (global system for mobile communication)





Overview YAMS Product Range VR903 (Accessory)



Tally Stick TS153 is for data transmission to and from the recorders of product range VR903. The data carrier TS153 may only be used within the VR903 family. Above the TS153 shown box is protecting the Tally Stick when not being used.



The 2nd. Illustration is showing the Tally Stick open, with the protective cap being removed. Clearly visible is the USB interface, suitable to the VR903 Reorder.



M22X is a external marker with 2 push buttons, for storing events that are needed to be stored in relation to time when they have occurred. The Marker M22X can only be used within the VR903 product range.